200 SERIES GLIDING WINDOWS



Table of Basic Unit Sizes Scale 1/8" = 1'-0" (1:96)

Unit Dimension	2'-11 ¹ /2" (902)	3'-11 1/2"	4'-11 ¹ /2" (1511)	5'-11 ¹ /2" (1816)
Minimum	3'-0"	4'-0"	5'-0"	6'-0"
Rough Opening	(914)	(1219)	(1524)	(1829)
Unobstructed Glass*	13 ¹¹ / ₁₆ " (348)	19 ¹¹ / ₁₆ " (500)	25 ¹¹ / ₁₆ " (652)	31 ¹¹ / ₁₆ " (805)
15 1/2" (445) 1-6" (457) 11 1/2" (292)	1 1	244 GW 4016	1 1	
1'-11 1/2" (597) 2'-0" (610) 17 1/2" (445)	244 GW 3020	244 GW 4020		
2'-11 1/2" (902) (902) 3'-0" (914) 29 1/2" (749)	→		→	→
	244 GW 3030	244 GW 4030	244 GW 5030†	244 GW 6030†
3'-5 1/2" (1054) 3'-6" (1067) 35 1/2" (902)	→			
	244 GW 3036	244 GW 4036	244 GW 5036†	244 GW 6036†
3'-11 1/2" (1207) 4'-0" (1219) 41 1/2" (1054)	→	→	→	→
	244 GW 3040	244 GW 4040†	244 GW 5040†	244 GW 6040†
$\begin{array}{c} 4^{1} \cdot 5 \ 1/2^{n} \\ (1359) \\ 4^{1} \cdot 6^{n} \\ (1372) \\ 47 \ 1/2^{n} \\ (1207) \end{array}$		→	→	
• • •		244 GW 4046†	244 GW 5046†	244 GW 6046†
$\begin{array}{c} 4^{1} 11^{1/2} \\ (1511) \\ 5^{1} 0^{n} \\ (1524) \\ 53^{1/2} \\ (1359) \end{array}$		→	→ □	→
· · · · · ·		244 GW 4050†	244 GW 5050†	244 GW 6050†



panel panel

(As viewed from the exterior.)

- * "Unobstructed Glass" measurement is for single sash only.
- Rough opening dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- "Unit Dimension" always refers to outside frame to frame dimension.
- Dimensions in parentheses are in millimeters.
- Picture window narrow jamb width is 3 1/16."
- When ordering, be sure to specify color desired: White or Sandtone. † These units meet or exceed the following dimensions:
- Clear Openable Area of 5.7 sq. ft., Clear Openable Width of 20" and Clear Openable Height of 24".