


400 SERIES GLIDING WINDOWS

Table of Basic Unit Sizes Scale 1/8" = 1'-0" (1:96)

Unit Dimension	2'-11 1/4" (895)	3'-11 1/4" (1200)	4'-11 1/4" (1505)	5'-11 1/4" (1810)
Minimum Rough Opening	3'-0" (914)	4'-0" (1219)	5'-0" (1524)	6'-0" (1829)
Unobstructed Glass*	12 9/16" (319)	18 9/16" (472)	24 9/16" (624)	30 9/16" (776)
1'-10 1/4" (565)	1'-11" (584)	1'-11 1/8" (589)		
	G32	G42		
2'-11 1/4" (895)	3'-0" (914)	27 1/8" (689)		
	G33	G43	G53	G63 ♦
3'-5 1/4" (1048)	3'-6" (1067)	33 1/8" (841)		
	G336	G436	G536 ♦	G636 ♦
3'-11 1/4" (1200)	4'-0" (1219)	39 1/8" (994)		
	G34	G44 ♦	G54 ♦	G64 ♦
4'-11 1/4" (1505)	5'-0" (1524)	51 1/8" (1299)		
	G35	G45 ♦	G55 ♦	G65 ♦



Venting Configuration

As viewed from the exterior. Passive sash will open after active sash has been opened.

* "Unobstructed Glass" measurement is for single sash only.
 ♦ These units meet or exceed the following dimensions: Clear Openable Area of 5.7 sq. ft., Clear Openable Width of 20" and Clear Openable Height of 24".
Rough opening dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
 *Unit Dimension" always refers to outside frame to frame dimension.
 Dimensions in parentheses are in millimeters.
 When ordering, be sure to specify color desired: White, Sandtone or Terratone."

Handle Locations – Operational Force = 8 lbs.

